


of the foregoing amendments and following remarks. Claims 1-6 are in the application. Claims 2-5 have been amended. No new matter has been added.

The Examiner rejected claims 2-5 under 35 U.S.C. §112, for indefiniteness. Applicant has amended claims 2-5 to overcome the Examiner's rejections. The Examiner stated that claims 1-6 are allowable over the prior art. Accordingly, Applicant submits that claims 1-6 as amended are now in condition for allowance. Early allowance is respectfully requested.

Respectfully submitted,  
MASATOSHI OHISHI ET AL.

COLLARD & ROE, P.C.  
1077 Northern Boulevard  
Roslyn, New York 11576  
(516) 365-9802  
ECR/ecr/jc  
Enclosure: Exhibit A  
RALIZAMD\Ohishi.vpd

  
Allison C. Collard, Reg. No. 22,532  
Edward R. Freedman, Reg. No. 26,048  
Elizabeth Collard Richter, Reg.No.35,103  
Attorney for Applicants

**CERTIFICATE OF FACSIMILE TRANSMISSION**

Fax No. 703-872-9314

I hereby certify that this correspondence is being sent by facsimile-transmission to the Assistant Commissioner for Patents, Washington, D.C. 20231, on October 4, 2002.

  
Elizabeth Collard Richter

EXHIBIT A

Marked-up copy of amended claims 2-5

2. (Amended) A light control type LED lighting equipment as set forth in claim 1, further comprising:

second control input generating means for generating one series of second control signal, a value of said second signal increasing or decreasing within a predetermined range by operation of the user;

common power control means for uniformly varying power supply amount for said first color LED group, said second color LED group and said third color LED group by uniformly increasing or decreasing amount of current value of said first color drive circuit, said second color drive circuit and said third color drive circuit depending upon a value of said second control input signal,

a hue of said LED aggregate lamp [substantially] maintained while brightness of the lighting is varied.

3. (Amended) A light control type lighting equipment as set forth in claim 2, wherein said first color drive circuit, said second color drive circuit and said third color drive circuit [are] have a constant current [type], and said individual power control means individually varies power supply amount for said first color LED group, said second color LED group and said third color LED group by a pulse width modulation method.

4. (Amended) A light control type LED lighting equipment as set forth in claim 1, further comprising:

second control input generating means for generating one series of second control signal, a value of said second control signal increasing or decreasing within a predetermined range by operation of the user;

common power control means for uniformly varying power supply amount for said first color LED group, said second color LED group and said third color LED group by varying output from said power source converting portion depending upon a value of said second control input signal,

a hue of said LED aggregate lamp [substantially] maintained while brightness of the lighting is varied.

5. (Amended) A light control type LED lighting equipment as set forth in claim 1, wherein said LED aggregate lamp portion, said alternating current power connecting portion, said power source converting portion, said first color drive circuit, said second color drive circuit, said third color drive circuit, said control output generating means including a control signal receiving portion and said individual power control means are mounted on the lighting equipment main body, said control input generating means including a control signal transmitting portion is mounted on a remote controller separated from said main body, said control signal transmitting portion being connected to said control signal receiving portion through a [ratio] radio transmission line.

